

Eaton M1H11TR2FHIRST2

Catalog Number: M1H11TR2FHIRST2

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' Rd pipe 1.0" OD, SI rbr, St-1 pt lt, Bnd rcp cnt hnd Ltn arstr brk stl intrph adl nmpl hnd ice shd grd cn Xarm mt brk Ex 14' cnt rd, Hz uprt, Rec hnd

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H11TR2FHIRST2
	UPC
	194006015479
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std C37.34
	IEEE Std 1247

Description	Electrical Ratings
Control rod and mechanism 28' round pipe 1.0" O.D.	Amperage Rating 900A
Crossarm material Steel - single point lift	Basic impulse level 110 kV
Insulator bolt pattern 2.25" BC	Number of phases Three-phase
Material type Silicone rubber	Voltage rating 15.5 kV
Switch type M-Force switch	
	M-Force Switch

[M-force - optional configurations](#)

Bonded reciprocating control handle, lightning arrester brkts, steel interphase rod, additional nameplate on handle, ice shields, grd connector on X-arm mtg brkt, extra 14' of control rod

[Mounting configuration \(M-force only\)](#)

Horizontal upright

[Operating handle configuration \(M-force only\)](#)

Reciprocating

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1H11TR2FHIRST2](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia