

Specifications

Eaton M1H41FC3FH1

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 3.00" BC, 28' 1" pipe w/Fbrgls top sect, C-A epx, Fbrgls-2 pt lft, Bonded recip cntrl hndl, Ltng arrstr brkts, Ex 7' of control rod, Hrз uprt, Recip hndl



Photo is representative



General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1H41FC3FH1
UPC	194006015554
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	22.5 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std C37.34 IEEE Std 1247

Description	
CONTROL ROD AND MECHANISM	28' 1" pipe w/fiberglass top section
CROSSARM MATERIAL	Fiberglass - two point lift
INSULATOR BOLT PATTERN	3.00" BC
MATERIAL TYPE	Cycloaliphatic epoxy
SWITCH TYPE	M-Force switch

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Bonded reciprocating control handle, lightning arrester brkts, extra 7' of control rod
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Reciprocating

Resources	
BROCHURES	M-Force Three-Phase Switch Catalog
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - M1H41FC3FH1

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

