

Specifications

Photo is representative

Eaton M1H51FC2EH

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' pipe w/cycloaliphatic Ins., Cycloaliphatic epoxy, Fbrgls-2 pt lft, Extension links, lightning arrester brkts, Horizontal upright, Reciprocating

General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1H51FC2EH
UPC	786689708696
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	22.5 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	330 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std C37.34 IEEE Std 1247

Description

CONTROL ROD AND MECHANISM	28' pipe w/cycloaliphatic insulator
CROSSARM MATERIAL	Fiberglass - two point lift
INSULATOR BOLT PATTERN	2.25" BC
MATERIAL TYPE	Cycloaliphatic epoxy
SWITCH TYPE	M-Force switch

M-Force Switch

M-FORCE - OPTIONAL CONFIGURATIONS	Extension links, lightning arrester brkts
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Reciprocating

Electrical Ratings

AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

Resources

BROCHURES	M-Force Three-Phase Switch Catalog
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - M1H51FC2EH

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

