

Specifications

Photo is representative

Eaton M1H51FP3H

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 3.00" BC, 28' pipe w/cycloaliphatic insulator, Porcelain, Fiberglass - 2 point lift, Lightning arrester brkts, Horizontal upright, Reciprocating

General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1H51FP3H
UPC	194006016865
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	23.5 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std C37.34 IEEE Std 1247

Description	
CONTROL ROD AND MECHANISM	28' pipe w/cycloaliphatic insulator
CROSSARM MATERIAL	Fiberglass - two point lift
INSULATOR BOLT PATTERN	3.00" BC
MATERIAL TYPE	Porcelain
SWITCH TYPE	M-Force switch

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Lightning arrester brkts
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Reciprocating

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

Resources	
BROCHURES	M-Force Three-Phase Switch Catalog
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - M1H51FP3H

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

