

Specifications

Photo is representative

Eaton M1H51TR2H

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' pipe w/Epoxy ins, SR ins, Stl 1-pt lft, lftg arr brkt, Hrzs up, Recip

General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1H51TR2H
UPC	194006221528
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	22.5 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 1247 IEEE Std C37.34

Description	
CONTROL ROD AND MECHANISM	28' pipe w/cycloaliphatic insulator
CROSSARM MATERIAL	Steel - single point lift
INSULATOR BOLT PATTERN	2.25" BC
MATERIAL TYPE	Silicone rubber
SWITCH TYPE	M-Force switch

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Lightning arrester brackets
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Reciprocating

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

Resources

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

