

Specifications

Eaton M1HA2SR22



Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (steel universal section), Silicone rubber, Steel - 2 point lift, Ex 14' of control rod, Horizontal upright, Torsional

Photo is representative



General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1HA2SR22
UPC	194006018203
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	23.9 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 1247 IEEE Std C37.34

Description	
CONTROL ROD AND MECHANISM	28' 1.5" pipe (steel universal section)
CROSSARM MATERIAL	Steel - two point lift
INSULATOR BOLT PATTERN	2.25" BC
MATERIAL TYPE	Silicone rubber
SWITCH TYPE	M-Force switch

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Extra 14' of control rod
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Torsional

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

Resources	
BROCHURES	M-Force Three-Phase Switch Catalog
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - M1HA2SR22



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

