

# Specifications

## Eaton M1HA2SR2HS



Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (stl uni), Sil rub, Stl - 2 pt lft, Ltng arrstr brkts, ice shld Hrzs up, Tors

Photo is representative



### General specifications

|                             |                                                      |
|-----------------------------|------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Cooper Power series M-Force three-phase switch |
| <b>CATALOG NUMBER</b>       | M1HA2SR2HS                                           |
| <b>UPC</b>                  | 194006091701                                         |
| <b>PRODUCT LENGTH/DEPTH</b> | 88 in                                                |
| <b>PRODUCT HEIGHT</b>       | 23.9 in                                              |
| <b>PRODUCT WIDTH</b>        | 22.4 in                                              |
| <b>PRODUCT WEIGHT</b>       | 0.001 lb                                             |
| <b>COMPLIANCES</b>          | Not Applicable                                       |
| <b>CERTIFICATIONS</b>       | IEEE Std 1247<br>IEEE Std C37.34                     |

| Description               |                                         |
|---------------------------|-----------------------------------------|
| CONTROL ROD AND MECHANISM | 28' 1.5" pipe (steel universal section) |
| CROSSARM MATERIAL         | Steel - two point lift                  |
| INSULATOR BOLT PATTERN    | 2.25" BC                                |
| MATERIAL TYPE             | Silicone rubber                         |
| SWITCH TYPE               | M-Force switch                          |

| M-Force Switch                                |                                          |
|-----------------------------------------------|------------------------------------------|
| M-FORCE - OPTIONAL CONFIGURATIONS             | Lightning arrester brackets, ice shields |
| MOUNTING CONFIGURATION (M-FORCE ONLY)         | Horizontal upright                       |
| OPERATING HANDLE CONFIGURATION (M-FORCE ONLY) | Torsional                                |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |

| Electrical Ratings  |             |
|---------------------|-------------|
| AMPERAGE RATING     | 900A        |
| BASIC IMPULSE LEVEL | 110 kV      |
| NUMBER OF PHASES    | Three-phase |
| VOLTAGE RATING      | 15.5 kV     |

| Resources                     |                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------|
| APPLICATION NOTES             | <a href="#">Line installation and protective equipment product application poster</a> |
| SPECIFICATIONS AND DATASHEETS | <a href="#">Eaton Specification Sheet - M1HA2SR2HS</a>                                |
|                               | <a href="#">Overhead line installation and protective equipment specifiers guide</a>  |
|                               | <a href="#">Line installation and protective equipment specifiers guide</a>           |



Eaton Corporation plc  
 Eaton House  
 30 Pembroke Road  
 Dublin 4, Ireland  
 Eaton.com

Follow us on social media to get the latest product and support information.

