

Specifications

Eaton M1HA2TP2HU1



Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (stl uni sec), Porc, STI - 1 pt lft, ltg arrst brkt, par grve conn, add 7' cntrl, Hz up, Tors

General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1HA2TP2HU1
UPC	194006092296
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	23.5 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std C37.34 IEEE Std 1247

Description	
CONTROL ROD AND MECHANISM	28' 1.5" pipe (steel universal section)
CROSSARM MATERIAL	Steel - single point lift
INSULATOR BOLT PATTERN	2.25" BC
MATERIAL TYPE	Porcelain
SWITCH TYPE	M-Force switch

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Lightning arrester brkts, parallel groove connector, additonal 7' of control rod
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Torsional

Resources	
APPLICATION NOTES	Line installation and protective equipment product application poster
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - M1HA2TP2HU1
	Line installation and protective equipment specifiers guide
	Overhead line installation and protective equipment specifiers guide

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

