

Specifications

Eaton M1HA2TR2BHS1



Photo is representative

Eaton Cooper Power series M-Force 3-ph switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe, SR, Stl 1-pt lft, prov xarm sup, ltng arr brkt, ice shld, ex 7' of cntrl rod, Hrzt uprt, Tors

General specifications

PRODUCT NAME	Eaton Cooper Power series M-Force three-phase switch
CATALOG NUMBER	M1HA2TR2BHS1
UPC	194006087926
PRODUCT LENGTH/DEPTH	88 in
PRODUCT HEIGHT	23.9 in
PRODUCT WIDTH	22.4 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std C37.34 IEEE Std 1247

Description	
CONTROL ROD AND MECHANISM	28' 1.5" pipe (steel universal section)
CROSSARM MATERIAL	Steel - single point lift
INSULATOR BOLT PATTERN	2.25" BC
MATERIAL TYPE	Silicone rubber
SWITCH TYPE	M-Force switch

Electrical Ratings	
AMPERAGE RATING	900A
BASIC IMPULSE LEVEL	110 kV
NUMBER OF PHASES	Three-phase
VOLTAGE RATING	15.5 kV

M-Force Switch	
M-FORCE - OPTIONAL CONFIGURATIONS	Provisions for crossarm support brackets, lightning arrester brackets, ice shield kits, Extra 7' of control rod
MOUNTING CONFIGURATION (M-FORCE ONLY)	Horizontal upright
OPERATING HANDLE CONFIGURATION (M-FORCE ONLY)	Torsional

Resources	
APPLICATION NOTES	Line installation and protective equipment product application poster
BROCHURES	M-Force Three-Phase Switch Catalog
	Eaton Specification Sheet - M1HA2TR2BHS1
SPECIFICATIONS AND DATASHEETS	Overhead line installation and protective equipment specifiers guide
	Line installation and protective equipment specifiers guide

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
 Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

Follow us on social media to get the latest product and support information.

