

# PRODUCT INFORMATION PACKET



Model No: E100115.00

Catalog No: E100115.00

ecoSaver™ General Purpose Motor, 0.25 HP, 1 Ph, 60 Hz, 115/230 V, 1800 RPM, 48 Frame, DP



Regal and LEESON are trademarks of Regal Rexnord Corporation or one of its affiliated companies.

©2025 Regal Rexnord Corporation, All Rights Reserved. MC017097E





## Nameplate Specifications

|                        |                   |                            |                   |
|------------------------|-------------------|----------------------------|-------------------|
| Phase                  | <b>1</b>          | Output HP                  | <b>0.25 Hp</b>    |
| Output KW              | <b>0.19 kW</b>    | Voltage                    | <b>115/230 V</b>  |
| Speed                  | <b>1725 rpm</b>   | Service Factor             | <b>1.35</b>       |
| Frame                  | <b>48</b>         | Enclosure                  | <b>Drip Proof</b> |
| Thermal Protection     | <b>Automatic</b>  | Efficiency                 | <b>68.5 %</b>     |
| Ambient Temperature    | <b>40 °C</b>      | Frequency                  | <b>60 Hz</b>      |
| Current                | <b>2.4/1.2 A</b>  | Power Factor               | <b>92.7</b>       |
| Duty                   | <b>Continuous</b> | Insulation Class           | <b>F</b>          |
| Design Code            | <b>N</b>          | KVA Code                   | <b>M</b>          |
| Drive End Bearing Size | <b>6203</b>       | Opp Drive End Bearing Size | <b>6203</b>       |
| UL                     | <b>Recognized</b> | CSA                        | <b>Y</b>          |
| CE                     | <b>Y</b>          | IP Code                    | <b>22</b>         |
| Number of Speeds       | <b>1</b>          |                            |                   |

## Technical Specifications

|                       |                                      |                       |                                   |
|-----------------------|--------------------------------------|-----------------------|-----------------------------------|
| Electrical Type       | <b>Capacitor Start Capacitor Run</b> | Starting Method       | <b>Across The Line</b>            |
| Poles                 | <b>4</b>                             | Rotation              | <b>Selective Counterclockwise</b> |
| Resistance Main       | <b>0 Ohms</b>                        | Mounting              | <b>Rigid Base</b>                 |
| Motor Orientation     | <b>Horizontal</b>                    | Drive End Bearing     | <b>Ball</b>                       |
| Opp Drive End Bearing | <b>Ball</b>                          | Frame Material        | <b>Rolled Steel</b>               |
| Shaft Type            | <b>NEMA 48</b>                       | Overall Length        | <b>10.12 in</b>                   |
| Frame Length          | <b>6.50 in</b>                       | Shaft Diameter        | <b>0.500 in</b>                   |
| Shaft Extension       | <b>1.5 in</b>                        | Assembly/Box Mounting | <b>F1 ONLY</b>                    |
| Outline Drawing       | <b>SS404327-675</b>                  | Connection Drawing    | <b>005053.40</b>                  |