

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency Three-Phase Product code : 12674869
Catalog # : 00512OT3H215TC-S

Frame	: 213/5TC	Locked rotor time	: 52s (cold) 29s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.61 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 39.3 A	Mounting	: F-1
LRC	: 7.0x(Code J)	Rotation ¹	: Both (CW and CCW)
No load current	: 3.20 A	Noise level ²	: 55.0 dB(A)
Rated speed	: 1180 rpm	Starting method	: Direct On Line
Slip	: 1.67 %	Approx. weight ³	: 118 lb
Rated torque	: 22.3 ft.lb		
Locked rotor torque	: 220 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 1.08 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.3	88.5	89.5	89.5	Max. traction	: 280 lb
Power Factor	0.32	0.56	0.67	0.74	Max. compression	: 398 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6208 ZZ	6206 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	22/10/2025			