

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency Three-Phase Product code : 15378605
Catalog # : 00718OT3P213T-SGH

Frame	: 213/5T	Locked rotor time	: 23s (cold) 13s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200 V	Altitude	: 1000 m.a.s.l.
Rated current	: 21.0 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 153 A	Mounting	: F-1
LRC	: 7.3x(Code H)	Rotation ¹	: Both (CW and CCW)
No load current	: 10.1 A	Noise level ²	: 59.0 dB(A)
Rated speed	: 1770 rpm	Starting method	: Direct On Line
Slip	: 1.67 %	Approx. weight ³	: 115 lb
Rated torque	: 22.3 ft.lb		
Locked rotor torque	: 200 %		
Breakdown torque	: 300 %		
Insulation class	: H		
Service factor	: 1.15		
Moment of inertia (J)	: 1.03 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	88.6	89.5	90.2	91.0	Max. traction	: 319 lb
Power Factor	0.39	0.65	0.78	0.83	Max. compression	: 434 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6208 ZZ	6206 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 1		
Checked by				
Date	22/10/2025			